



SAFETY DATA SHEET

SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION

Product ID: MF-1001LVA
Product Name: MAGMAFLO 100% Solids Epoxy, A-Side
Revision Date: April 26, 2023 **Date Printed:** April 26, 2023
Version: Supersedes **Date:** NA
Manufacturer's Name: DESERT POLYMER FLOORING, INC.
Address: 77583 EL DUNA CT., UNIT F, PALM DESERT, CA 92211
Emergency Phone: Chemtrec:800-424-9300 (account: CCN1217) OR International:703-527-3887
(account: CCN1217)
Information Phone Number: (847) 659-0300
Fax: (847) 659-0310
Product/Recommended Uses: For Further Information, Refer to the Product Technical Data Sheet.

SECTION 2) HAZARDS IDENTIFICATION

Classification:

Acute aquatic toxicity - Category 2
Chronic aquatic toxicity - Category 2
Eye Irritation - Category 2A
Skin Irritation - Category 2
Skin Sensitizer - Category 1B

Pictograms:



Signal Word:

Warning

Hazardous Statements - Health:

H319 - Causes serious eye irritation
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

Hazardous Statements - Environmental:

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements – General:

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements – Prevention:

P273 - Avoid release to the environment.



- P264 - Wash thoroughly after handling.
- P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
- P272 - Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements – Response:

- P391 - Collect spillage.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 - If eye irritation persists: Get medical advice/attention.
- P302 + P352 - IF ON SKIN: Wash with plenty of water.
- P321 - Specific treatment (see section 4 on this SDS).
- P362 + P364 - Take off contaminated clothing. And wash it before reuse.
- P333 + P313 - If skin irritation or a rash occurs: Get medical advice/attention.

Precautionary Statements - Storage:

No precautionary statement available.

Precautionary Statements - Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant.

SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS

| CAS | Chemical Name | % by Weight |
|--------------|--------------------------------------|-------------|
| 0025068-38-6 | BISPHENOL A EPOXY RESIN | 26% - 49% |
| 0025085-99-8 | BISPHENOL A EPOXY RESIN | 23% - 42% |
| 0017557-23-2 | DIGLYCIDYL ETHER OF NEOPENTYL GLYCOL | 8% - 14% |
| 0068609-97-2 | ALKYL GLYCIDYL ETHER | 7% - 12% |
| 0000104-40-5 | NONYLPHENOL | 4% - 7% |

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.
If exposed/feel unwell/concerned: Call a POISON CENTER/doctor.

Skin Contact

Rinse/wash with lukewarm, gently flowing water and mild soap for 15-20 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.
IF exposed or concerned: Get medical advice/attention.

Eye Contact

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If vomiting occurs naturally, lie on your side, in the recovery position. Give 1 or 2 glasses of milk or water to drink and refer person to medical personnel. Do not give anything by mouth to an unconscious person.



SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, carbon dioxide water spray or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

Specific Hazards in Case of Fire

Excessive pressure or temperature may cause explosive rupture of containers.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear. Care should always be exercised in dust/mist areas.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled material. Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Appropriate dust or face mask to eliminate breathing foam dust particulates.

Personal Precautions

Avoid breathing vapors. Avoid contact with skin, eyes or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Soak up material with absorbent and shovel into a chemical waste container. Cover container, but do not seal, and remove from work area. Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, call CHEMTREC (Chemical Transportation Emergency Center) at 800-424-9300.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking, and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

Individuals with existing respiratory disease such as chronic bronchitis, emphysema, or asthma should not be exposed.



Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, and incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous. Store in tightly sealed containers to protect from atmospheric moisture. Store in a cool dry area. Store liquid in containers above ground and surround by dikes to contain spills or leaks. Do not cut, drill, grind, weld, or perform similar operations on or near containers.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene, or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory Protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers. Use either an atmosphere supplying respirator or an air-purifying respirator for organic vapors.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

| Chemical Name | OSHA TWA (ppm) | OSHA TWA (mg/m3) | OSHA STEL (ppm) | OSHA STEL (mg/m3) | OSHA TABLES (Z1, Z2, Z3) | OSHA Carcinogen | OSHA Skin Designation | NIOSH TWA (ppm) |
|-------------------------|----------------|------------------|-----------------|-------------------|--------------------------|-----------------|-----------------------|-----------------|
| No applicable chemicals | - | - | - | - | - | - | - | - |

| Chemical Name | NIOSH TWA (mg/m3) | NIOSH STEL (ppm) | NIOSH STEL (mg/m3) | NIOSH Carcinogen | ACGIH TWA (ppm) | ACGIH TWA (mg/m3) | ACGIH STEL (ppm) | ACGIH STEL (mg/m3) |
|-------------------------|-------------------|------------------|--------------------|------------------|-----------------|-------------------|------------------|--------------------|
| No applicable chemicals | - | - | - | - | - | - | - | - |

| Chemical Name | ACGIH Carcinogen | ACGIH TLV Basis | ACGIH Notations |
|-------------------------|------------------|-----------------|-----------------|
| No applicable chemicals | - | - | - |



SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties:

| | |
|------------------|-------------|
| Density | 9.16 lb/gal |
| Specific Gravity | 1.10 |
| VOC Regulatory | 0.00 lb/gal |

| | |
|-------------------------|-------------------|
| VOC Part A & B Combined | N.A. |
| Appearance | Liquid |
| Odor Threshold | N.A. |
| Odor Description | Mild-chemical |
| pH | N.A. |
| Water Solubility | N.A. |
| Flammability | N/A |
| Flash Point Symbol | N.A. |
| Flash Point | 200 °C |
| Viscosity | N.A. |
| Lower Explosion Level | N.A. |
| Upper Explosion Level | N.A. |
| Vapor Pressure | N.A. |
| Vapor Density | Heavier than air |
| Freezing Point | N.A. |
| Melting Point | N.A. |
| Low Boiling Point | 250 °C |
| High Boiling Point | N.A. |
| Auto Ignition Temp | N.A. |
| Decomposition Pt | N.A. |
| Evaporation Rate | Slower than ether |
| Coefficient Water/Oil | N.A. |

SECTION 10) STABILITY AND REACTIVITY

Stability

Material is stable at standard temperature and pressure.

Conditions to Avoid

Heat, high temperature, open flame, sparks, and moisture. Contact with incompatible materials in a closed system will cause buildup of pressure.

Hazardous Reactions/Polymerization

Will not occur but aliphatic amine will cause irreversible polymerization with considerable heat build up.

Incompatible Materials

This product will react with materials such as amines, alkalis and acids. Avoid strong oxidizing agents. Some reactions can be violent.

Hazardous Decomposition Products

Combustion products: organic vapors and thermal decomposition fragments.



SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

Repeated skin contact may cause a persistent irritation or dermatitis. May also aggravate an existing skin condition.
Causes skin irritation

Serious Eye Damage/Irritation

Causes serious eye irritation

Respiratory/Skin Sensitization

Exposure may cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath, and a dry cough. The effects of acute exposure may be delayed in onset up to 12-24 hours. Repeated exposure above current occupational limits may cause an allergic sensitization of the respiratory tract. This is characterized by an asthma-like response upon re-exposure to the chemical. The symptoms may include coughing, wheezing, shortness of breath and chest tightness.
May cause an allergic skin reaction

Carcinogenicity

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Repeated exposure generally aggravates the following medical conditions: Cardiovascular disease and Chronic respiratory disease. Based on available data, the classification criteria are not met.

Aspiration Hazard

Based on available data, the classification criteria are not met.

Acute Toxicity

Ingestion: Irritation or chemical burns of the mouth, pharynx, esophagus, and stomach can develop following ingestion. Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Potential Health Effects - Miscellaneous

0025068-38-6 BISPHEENOL A EPOXY RESIN

The following medical conditions may be aggravated by exposure: skin disorders. Laboratory studies with rats have shown that petroleum distillates can cause kidney damage and kidney or liver tumors. These effects were not seen in similar studies with **quin**

0068609-97-2 ALKYL GLYCIDYL ETHER

The following medical conditions may be aggravated by exposure: allergies, eczema, skin disorders. Irritating to the mouth, throat and stomach. Potential skin sensitizer that may cause allergic reactions and contact dermatitis resulting in severe irritation, dryness, and cracking of the skin.

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Toxic to aquatic life

Toxic to aquatic life with long lasting effects

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

**Other Adverse Effects**

No data available.

Bioaccumulative Potential

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS**Waste Disposal**

Under RCRA, it is the responsibility of the user of the product, to determine the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state, and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION**U.S. DOT Information**

Not regulated

IMDG Information

UN/NA #: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

Hazard Class: 9

Packing Group: III

Placard: Class 9

Marine Pollutant: Yes

IATA Information

UN/NA #: 3082

UN Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

Hazard Class: 9

Packing Group: III

SECTION 15) REGULATORY INFORMATION

| CAS | Chemical Name | % By Weight | Regulation List |
|--------------|--------------------------------------|-------------|---------------------------|
| 0025068-38-6 | BISPHENOL A EPOXY RESIN | 26% - 49% | DSL,SARA312,TSCA |
| 0025085-99-8 | BISPHENOL A EPOXY RESIN | 23% - 42% | DSL,SARA312,TSCA |
| 0017557-23-2 | DIGLYCIDYL ETHER OF NEOPENTYL GLYCOL | 8% - 14% | DSL,SARA312,VOC,TSCA |
| 0068609-97-2 | ALKYL GLYCIDYL ETHER | 7% - 12% | DSL,SARA312,TSCA |
| 0000104-40-5 | NONYLPHENOL | 4% - 7% | SARA313, DSL,SARA312,TSCA |

SECTION 16) OTHER INFORMATION**OTHER INFORMATION**

Note: As per GHS, category 1 is the greatest level of hazard within each class.

GLOSSARY

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; CA Prop65- California Proposition 65; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration;



LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS Workplace Hazardous Materials Information System.

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec – Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL- Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC – Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

VERSION 1.0:

Revision Date: April 26, 2023

DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.